

## SAFETY DATA SHEET

### 1 - IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**Identification of the substance or preparation:**

Name: FLUO MARKER

Product code: 13131-+

**Company/undertaking identification:**

Registered company name: SOPPEC.

Address: ZI.16440.NERSAC.FRANCE.

Telephone: 0033545909312. Fax:0033545905867. Telex:.

www.soppec.com

**Emergency telephone: 0033145425959.**

Association/Organisation: INRS, Service du Contrôle des produits .

**Use of the substance/preparation:**

Forestry marking paint in aerosol dispensers for professional use

Forestry marker

### 2 - HAZARDS IDENTIFICATION

This product is classed: Extremely flammable.

Repeated exposure may cause skin dryness or cracking.

Vapors may cause drowsiness and dizziness.

**Preparation classification:**


Extremely flammable.

R 12	Extremely flammable.
R 66	Repeated exposure may cause skin dryness or cracking.
R 67	Vapours may cause drowsiness and dizziness.

**Other data:**

PRESSURISED CONTAINER

### 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Full text of risk phrases appearing in section 3: see section 16.

**Hazardous substances present on their own:**

(present in the preparation at a sufficient concentration to give it the toxicological characteristics it would have in a 100% pure state)

This preparation contains no hazardous substance in this category.

**Other substances representing a hazard:**

No known substance in this category present.

**Substances present at a concentration below the minimum danger threshold:**

INDEX	CAS	EC	Name	Symb.	R:	%
607-022-00-5	141-78-6	205-500-4	ETHYL ACETATE	Xi F	11 36 66 67	10 <= x % < 25

**Other substances with occupational exposure limits:**

INDEX	CAS	EC	Name	Symb.	R:	%
601-003-00-5	74-98-6	200-827-9	PROPANE	F+	12	10 <= x % < 25
601-004-00-0	106-97-8	203-448-7	BUTANE	F+	12	10 <= x % < 25

**Other components:**

INDEX	CAS	EC	Name	Symb.	R:	%
	64742-49-0		NAPHTA LEGER HYDROTRAITE	Xn	65 10 66 67	10 <= x % < 25
	64742-48-9	265-150-3	NAPHTA PETROLIER LOURD HYDROTRAITE	Xn	65 10 66 67	2.5 <= x % < 10

#### 4 - FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing in an unconscious person.

**In the event of exposure by inhalation:**

If a large quantity is inhaled, move the patient into the fresh air and keep him/her warm and still.

**In the event of splashes or contact with eyes:**

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.

Refer the patient to an ophthalmologist, in particular if there is any redness, pain or visual impairment.

**In the event of splashes or contact with skin:**

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

DO NOT use solvents or thinners.

**In the event of swallowing:**

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

If swallowed accidentally, call a doctor to assess the need for monitoring and subsequent treatment in hospital. Show him the label.

N/A

#### 5 - FIRE-FIGHTING MEASURES

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

**Suitable extinguishing media:**

Carbon dioxide, chemical powders, foams, and other extinguishing gases.

In the event of fire, use specifically suitable extinguishing agents. Never use water.

**Extinguishing media which must not be used for safety reasons:**

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Do not use compressed air during filling, emptying or handling.

**Special protective equipment for fire-fighters:**

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

#### 6 - ACCIDENTAL RELEASE MEASURES

**Personal precautions:**

On account of the organic solvents contained in the preparation, eliminate sources of ignition and ventilate the premises.

Avoid inhaling the vapors.

Consult the safety measures listed under headings 7 and 8.

**Environmental precautions:**

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

Use drums to dispose of waste recovered in accordance with applicable regulations (see heading 13).

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

**Methods for cleaning up:**

Clean preferably with a detergent, do not use solvents.

#### 7 - HANDLING AND STORAGE

The regulations relating to storage premises apply to workshops where the product is handled.

**Handling:**

Handle in well-ventilated areas.

The vapors are denser than air. They can spread along the ground and form explosive mixtures with air

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

**Fire prevention:**

Use the product in premises where there are no naked flames or other sources of ignition and have protected electrical equipment

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

**Recommended equipment and procedures:**

- For personal safety, see §8.
- Observe precautions stated on label and also industrial safety regulations
- Packages which have been opened must be reclosed carefully and stored in an upright position
- Avoid inhaling vapors.

**Prohibited equipment and procedures:**

- Smoking, eating and drinking are prohibited in premises where the preparation is used
- Never open the packages under pressure
- Do not pierce or burn, even after use.

**Storage:**

- Keep the container tightly closed in a dry, well-ventilated place
- Keep away from all sources of ignition - do not smoke.
- Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.
- Keep out of reach of children
- The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.
- Keep the container in a well ventilated place

**8 - EXPOSURE CONTROLS/PERSONAL PROTECTION**

Use personal protection equipment as per Directive 89/686/EEC.

**Technical measures:**

- Ensure adequate ventilation, if possible with extractor fans at work posts and appropriate general extraction.
- If this ventilation is insufficient to maintain the concentration of solvent vapors below the exposure limits, wear breathing apparatus

**Exposure limit values per INRS ED 984:**

France	VME-ppm:	VME-mg/m3:	VLE-ppm:	VLE-mg/m3:	Notes:	TMP N°:
141-78-6	400	1400	-	-	-	84
106-97-8	800	1900	-	-	-	-

**Exposure limit values (2003-2006):**

UKWELs	TWA:	STEL:	Ceiling:	Definition:	Criterion:
141-78-6	200 ppm	400 ppm	-	-	-
106-97-8	600 ppm	750 ppm	-	-	-
UK/OES	TWA:	STEL:	Ceiling:	Definition:	Criterion:
141-78-6	200 ppm	400 ppm	-	-	-
106-97-8	600 ppm	750 ppm	-	-	-
ACGIH/TLV	TWA:	STEL:	Ceiling:	Definition:	Criterion:
141-78-6	400 ppm	-	-	-	-
106-97-8	1000 ppm	-	-	-	-
74-98-6	1000 ppm	-	-	-	-
Germany/MAK	TWA:	STEL:	Ceiling:	Definition:	Criterion:
141-78-6	400 ppm	800 ppm	-	-	-
106-97-8	1000 ppm	4000 ppm	-	-	-
74-98-6	1000 ppm	4000 ppm	-	-	-

**Respiratory protection:**

Where workers encounter concentrations higher than the exposure limits, they must wear suitable, approved masks.

**Hand protection:**

- Protective creams may be used for exposed skin, but they should not be applied after contact with the product.
- In the event of prolonged or repeated contact with the hands, use appropriate gloves.

**Eye and face protection:**

Use eye protectors designed to protect against liquid splashes

**Skin protection:**

For further information, see § 11 of S.D.S. - Toxicological information.

**9 - PHYSICAL AND CHEMICAL PROPERTIES****General information:**

Physical state:	viscous liquid
-----------------	----------------

**Important health, safety and environmental information:**

pH of the substance or preparation:	not relevant.
-------------------------------------	---------------

The pH is impossible to measure or its value is not relevant.

Boiling point/boiling range:	not specified.
Flash point interval:	Flash point: < 0°C. and distillation temperature <= 35°C.
vapour pressure:	not relevant.
Density:	< 1
water solubility:	Insoluble.

**Other information:**

melting point/melting range:	not specified.
Self-ignition temperature:	not specified.
Decomposition point/decomposition range :	not specified.

Colours: see caps

Form: aerosol spray dispensers using pressurised liquefied gas ( isobutane/propane mixture )

**10 - STABILITY AND REACTIVITY**

When exposed to high temperatures, the preparation may release dangerous decomposition products such as carbon monoxide and dioxide, smoke and nitrogen oxide

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

**11 - TOXICOLOGICAL INFORMATION**

No data is available regarding the preparation itself.

Exposure to vapors from solvents contained in the preparation beyond the exposure limits stated may produce effects harmful to health, such as:

Irritation of mucous membrane and respiratory system, kidneys, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Prolonged or repeated contact with the preparation may strip the skin of its natural oil and thus cause non-allergic dermatitis on contact and absorption through the epidermis.

Splashes in the eyes may cause irritation and reversible damage

**12 - ECOLOGICAL INFORMATION**

No ecological data on the product itself is available.

The product must not be allowed to run into drains or waterways.

**Other adverse effects:**

N/A

no labelling related to the environment

**13 - DISPOSAL CONSIDERATIONS**

Do not pour into drains or waterways.

**Waste:**

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging:**

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

**Codes of wastes (Decision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous waste) :**

16 05 04 \* gases in pressure containers (including halons) containing dangerous substances

**14 - TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2007 - IMDG 2006 - ICAO/IATA 2007).

UN1950=AEROSOLS, flammable

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	
	2	5F	-	2.1	-	LQ2	190 327 625	
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.		
	SP63	SP63	-	SP277	F-D,S-U	63 190 277 327 959		
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note

	2.1	-	-	Forbidden	Forbidden	203	150 Kg	A1 A145 A153	
	2.1	-	-	-	-	-	-	-	

## 15 - REGULATORY INFORMATION

This preparation was classified in compliance with the directive known as <All preparations> 1999/45/EC and its adaptations

In addition directive 2004/73/EC with the 29° adaptation of directive 67/548/EEC (Hazardous substances) have been taken into account.

### Preparation classification:



Extremely flammable.

### Particular hazards associated with the preparation and safety recommendations:

R 12	Extremely flammable.
R 66	Repeated exposure may cause skin dryness or cracking.
R 67	Vapours may cause drowsiness and dizziness.
S 16	Keep away from sources of ignition - No smoking.
	Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C.
	Do not pierce or burn, even after use.
	Do not spray on a naked flame or any incandescent material.
S 23	Ne pas respirer les vapeurs.
S 24	Avoid contact with skin.
S 2	Keep out of the reach of children.
S 51	Use only in well-ventilated areas.
	Keep away from and do not use in the reach of any flame or source of heat, ignition or sparks, and away from any electrical apparatus in use.
	Not to be used for any usage other than those specified.
	Do not use in a confined space.
	Reserved for professional users.

## 16 - OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The product must not be used for any purposes other than those specified under heading 1 without first obtaining written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information given on this safety data sheet must be regarded as a description of the safety requirements relating to our product and not a guarantee of its properties

### Full text of risk phrases appearing in section 3:

R 10	Flammable.
R 11	Highly flammable.
R 12	Extremely flammable.
R 36	Irritating to eyes.
R 65	Harmful: may cause lung damage if swallowed.
R 66	Repeated exposure may cause skin dryness or cracking.
R 67	Vapours may cause drowsiness and dizziness.